

0394	0393	0391	9016
0394-0-15-XX-07-XX-10-0 Solder mount in 3,05 min. mounting hole	0393-0-15-XX-07-XX-10-0 Solder mount in 3,66 min. mounting hole	0391-0-15-XX-07-XX-10-0 Solder mount in 4,04 min. mounting hole	9016-0-15-XX-07-XX-10-0 Press-fit in 3,33 mounting hole

0493	0490	0616	0387
0493-0-15-XX-07-XX-10-0 Press-fit in 3,66 mounting hole	0490-0-15-XX-07-XX-04-0 Press-fit in 3,66 mounting hole	0616-0-18-XX-07-XX-10-0 Press-fit in 3,66 mounting hole	0387-0-15-XX-07-XX-04-0 Solder mount in 1,60 min. mounting hole

0370	4040	0491	9214
0370-0-19-XX-07-XX-10-0 #18 Gage crimp barrel	4040-0-19-XX-07-XX-10-0 Wire Termination	0491-0-19-XX-07-XX-04-0 For use in stackable patch cords	9214-0-15-XX-07-XX-10-0 Solder mount in 2,11 min. mounting hole

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>PART MANUFACTURED IN INCHES, METRIC FOR REF ONLY</p> <p>TOLERANCES ON: LENGTHS: ± 0,13 DIAMETERS: ± 0,05 ANGLES: ± 2°</p>	<p>ORDER CODE: <u>XXXX</u> - X - 1X - <u>XX</u> - 07 - <u>XX</u> - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL 80 5,08µm TIN OVER NICKEL ◊ 15 0,25µm GOLD OVER NICKEL ◊</p> <p>SPECIFY CONTACT FINISH: →</p> <p>01 5,08µm TIN/LEAD OVER NICKEL 80 5,08µm TIN OVER NICKEL ◊ 27 0,76µm GOLD OVER NICKEL ◊</p> <p style="text-align: center;">CONTACT #07 CONTACT (DATA ON PAGE 214)</p>
--	--

