

<p><b>0394</b></p> <p><b>0394-0-15-XX-07-XX-10-0</b> Solder mount in .120 min. mounting hole</p>	<p><b>0393</b></p> <p><b>0393-0-15-XX-07-XX-10-0</b> Solder mount in .144 min. mounting hole</p>	<p><b>0391</b></p> <p><b>0391-0-15-XX-07-XX-10-0</b> Solder mount in .159 min. mounting hole</p>	<p><b>9016</b></p> <p><b>9016-0-15-XX-07-XX-10-0</b> Press-fit in .131 mounting hole</p>
<p><b>0493</b></p> <p><b>0493-0-15-XX-07-XX-10-0</b> Press-fit in .144 mounting hole</p>	<p><b>0490</b></p> <p><b>0490-0-15-XX-07-XX-04-0</b> Press-fit in .144 mounting hole</p>	<p><b>0616</b></p> <p><b>0616-0-18-XX-07-XX-10-0</b> Press-fit in .144 mounting hole</p>	<p><b>0387</b></p> <p><b>0387-0-15-XX-07-XX-04-0</b> Solder mount in .063 min. mounting hole</p>
<p><b>0370</b></p> <p><b>0370-0-19-XX-07-XX-10-0</b> #18 Gage crimp barrel</p>	<p><b>4040</b></p> <p><b>4040-0-19-XX-07-XX-10-0</b> Wire Termination</p>	<p><b>0491</b></p> <p><b>0491-0-19-XX-07-XX-04-0</b> For use in stackable patch cords</p>	<p><b>9214</b></p> <p><b>9214-0-15-XX-07-XX-10-0</b> Solder mount in .083 min. mounting hole</p>

**SPECIFICATIONS**

**SHELL MATERIAL:**  
Brass Alloy 360, 1/2 Hard

**CONTACT MATERIAL:**  
Beryllium Copper Alloy 172, HT

**DIMENSION IN INCHES**  
**TOLERANCES ON:**  
LENGTHS: ±.005  
DIAMETERS: ±.002  
ANGLES: ± 2°

**ORDER CODE: XXXX - X - 1X - XX - 07 - XX - XX - 0**

**BASIC PART #**

**SPECIFY SHELL FINISH:**  
**01** 200µ" TIN/LEAD OVER NICKEL  
**80** 200µ" TIN OVER NICKEL   
**15** 10µ" GOLD OVER NICKEL

**SPECIFY CONTACT FINISH:**  
**01** 200µ" TIN/LEAD OVER NICKEL  
**80** 200µ" TIN OVER NICKEL   
**27** 30µ" GOLD OVER NICKEL



**CONTACT**

#07 CONTACT (DATA ON PAGE 214)