



DUAL-IN-LINE TURRET HEADERS

Solder Tail and Wrapost Open Frame

Series 170, 173

170...001 173...001

- Series 170 & 173 DIL headers are equipped with turret heads for wiring applications.
- Series 170 terminations are pluggable .020" dia. solder tails MM #0700, See page 174 for details. Series 173 terminations are three level wraposts MM #0730. See page 185 for details.
- Insulators are high temperature thermoplastic.

Total number of pins				Quantity per tube	Ordering Information				
	A	B	C		Solder Tail	3 Level Wrapost			
	10	0.5	0.2		0.3	41	170-XX-210-00-001000	173-10-210-00-001000	
4	0.2	0.3	0.4	102	170-XX-304-00-001000	173-10-304-00-001000			
6	0.3	0.3	0.4	67	170-XX-306-00-001000	173-10-306-00-001000			
8	0.4	0.3	0.4	50	170-XX-308-00-001000	173-10-308-00-001000			
10	0.5	0.3	0.4	40	170-XX-310-00-001000	173-10-310-00-001000			
14	0.7	0.3	0.4	28	170-XX-314-00-001000	173-10-314-00-001000			
16	0.8	0.3	0.4	25	170-XX-316-00-001000	173-10-316-00-001000			
18	0.9	0.3	0.4	22	170-XX-318-00-001000	173-10-318-00-001000			
20	1.0	0.3	0.4	20	170-XX-320-00-001000	173-10-320-00-001000			
22	1.1	0.3	0.4	18	170-XX-322-00-001000	173-10-322-00-001000			
24	1.2	0.3	0.4	16	170-XX-324-00-001000	173-10-324-00-001000			
28	1.4	0.3	0.4	14	170-XX-328-00-001000	173-10-328-00-001000			
20	1.0	0.4	0.5	20	170-XX-420-00-001000	173-10-420-00-001000			
22	1.1	0.4	0.5	18	170-XX-422-00-001000	173-10-422-00-001000			
24	1.2	0.4	0.5	16	170-XX-424-00-001000	173-10-424-00-001000			
28	1.4	0.4	0.5	14	170-XX-428-00-001000	173-10-428-00-001000			
32	1.6	0.4	0.5	12	170-XX-432-00-001000	173-10-432-00-001000			
24	1.2	0.6	0.7	16	170-XX-624-00-001000	173-10-624-00-001000			
28	1.4	0.6	0.7	14	170-XX-628-00-001000	173-10-628-00-001000			
32	1.6	0.6	0.7	12	170-XX-632-00-001000	173-10-632-00-001000			
36	1.8	0.6	0.7	11	170-XX-636-00-001000	173-10-636-00-001000			
40	2.0	0.6	0.7	10	170-XX-640-00-001000	173-10-640-00-001000			
42	2.1	0.6	0.7	9	170-XX-642-00-001000	173-10-642-00-001000			
48	2.4	0.6	0.7	8	170-XX-648-00-001000	173-10-648-00-001000			
50	2.5	0.6	0.7	8	170-XX-650-00-001000	173-10-650-00-001000			
52	2.6	0.6	0.7	7	170-XX-652-00-001000	173-10-652-00-001000			
50	2.5	0.9	1.0	8	170-XX-950-00-001000	173-10-950-00-001000			
52	2.6	0.9	1.0	7	170-XX-952-00-001000	173-10-952-00-001000			
64	3.2	0.9	1.0	6	170-XX-964-00-001000	173-10-964-00-001000			
SPECIFY PLATING CODE XX=					10	90	40		
Pin Plating					10μ" Au	200μ" Sn/Pb	200μ" Sn		

For RoHS compliance select plating code.

XX= Plating Code
See Below