



SECTION A-A

NOTES:

1. MATERIAL: PVC, SOFT (RMS-55).
COLOR: BLUE, TRANSLUCENT.
2. FOR "SPASH PROOF SEAL"
RECOMMENDED WIRE OD=.088 TO .120
(2.2 TO 3.1).

E			FILE NO. WAS ISFPP			SM 10.30.02			TITLE: INSULATING SLEEVE FOR PIN PLUG			DWG IN		IN (MM)		QR	
D			RMS-55 WAS RMS-126			RG 09.26.01			TOLERANCES UNLESS NOTED			DWN: P.B.		APP:		FINAL	
C			ADDED RMS-126 TO MATERIAL NOTE; CHANGED FILE NO. AND TITLE BLOCK			SM 06.26.01			.XX=±.010			FILE # 224210		DT: 03-23-95		DT:	
B			CONV. TO ACAD; COLOR CHANGE-SEE ECN 128			PB 03.23.95			.XXX=±.005			MAT'L: SEE NOTES		RE:		PART #	
A			INSIDE DIA. .085 WAS .090			JP 09.12.90			FRAC=±1/64			RICHCO, INC.		RICHCO INC.		224210	
REV			DESCRIPTION			ENGR DATE			ANG=±1'			PO BOX 804238, CHICAGO, 60680		(773) 539-4060		PRINT TYPE CA	