

FLKM 14-PA-SLC500/OUT

Order No.: 2293459

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2293459>VARIOFACE front adapter, 2 x 8 channels can be connected, for
Allen-Bradley SLC 500, 1746 OB16, OV16, OG16 and IG16**Commercial data**

EAN	4017918108854
Pack	1 Pcs.
Customs tariff	85369010
Weight/Piece	0.0602 KG
Catalog page information	Page 164 (IF-2007)

Product notesWEEE/RoHS-compliant since:
06/04/2007

<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data**General**

Nominal voltage U_N	120 V AC/DC
Connection type, plug connector	Flat-ribbon cable plug connector in acc. with IEC 60603-13
Number of plug connectors	2
No. of positions, plug connector	14

Number of positions	14
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any
Standards/regulations	IEC 60664
	DIN EN 50178
	IEC 62103
Max. permissible current	Per path 1 A
Max. permissible total current	Per byte 2 A (during supply via a connector)
Pollution degree	1
Surge voltage category	II

Certificates / Approvals

Approval logo




requested approbations

Certification	CUL, GOST, UL
---------------	---------------

Drawings

Circuit diagram



Connection scheme FLKM 14-PA-SLC500/OUT

Address

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg, Germany
Phone +49 5235 3 00
Fax +49 5235 3 41200
<http://www.phoenixcontact.de>



© 2008 Phoenix Contact
Technical modifications reserved;