

SPECIFICATIONS

Properties
Resin Type
Conductive
Average Surface Resistivity
Humidity Independent
Provides ESD Shielding
Temperature Tolerance
Melting Point

Typical Values

Polypropylene Permanently


10E2 - 10E4 ohms

Yes Yes

-17° F to +230° F

324° F

Features





- Many sizes available
- Shipped knocked-down; easy to assemble
- Conductive 10E2 10E4 ohm material provides reliable path-toground
- Superior strength and durability; made from extruded, high impact polypropylene materials
- Chemical and moisture resistant
- Ideal for use where corrugated and/or paper products cannot be used
- · Economical alternative to injection molded products
- Reusable, ensuring best value*
- · Made in America

Item No.	Size O.D L x W x D	Item No.	Size O.D L x W x D
38900	12 x 2 x 4	38905	18 x 6 x 4
38901	12 x 4 x 4	38906	18 x 8 x 4
38902	12 x 6 x 4	38910	24 x 2 x 4
38903	12 x 8 x 4	38907	24 x 4 x 4
38909	18 x 2 x 4	38908	24 x 6 x 4
38904	18 x 4 x 4		

RoHS Compliance Statement

None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Protektive Pak Inc. letter on-line at ProtektivePak.com.



Plastek™ Open Bin Boxes

PROTEKTIVE PAK

PROTEKTIVE PAK 13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578, FAX (909) 363-7331 www.protektivepak.com

DRAWING NUMBER 38900 **DATE:** 8/07