






ASSEMBLY ITEM NUMBER	PART CHARACTERISTICS FOR RIGHT ANGLE	
	NUMBER OF POSITION	PLATING OPTION
43650-0200	02	A
43650-0201	02	B
43650-0202	02	C
43650-0300	03	A
43650-0301	03	B
43650-0302	03	C
43650-0400	04	A
43650-0401	04	B
43650-0402	04	C
43650-0500	05	A
43650-0501	05	B
43650-0502	05	C
43650-0600	06	A
43650-0601	06	B
43650-0602	06	C
43650-0700	07	A
43650-0701	07	B
43650-0702	07	C
43650-0800	08	A
43650-0801	08	B
43650-0802	08	C
43650-0900	09	A
43650-0901	09	B
43650-0902	09	C
43650-1000	10	A
43650-1001	10	B
43650-1002	10	C
43650-1100	11	A
43650-1101	11	B
43650-1102	11	C
43650-1200	12	A
43650-1201	12	B
43650-1202	12	C

CKT. NO.	DIM. "A"	DIM. "B"	DIM. "C"
2	.270/(16.85)	.118/(3.00)	NA
3	.388/(19.85)	.236/(16.00)	NA
4	.506/(12.85)	.354/(19.00)	.185/(4.70)
5	.624/(15.85)	.472/(12.00)	.303/(17.70)
6	.742/(18.85)	.591/(15.00)	.421/(10.70)
7	.860/(12.85)	.709/(18.00)	.539/(13.70)
8	.978/(24.85)	.827/(21.00)	.657/(16.70)
9	1.096/(12.85)	.945/(24.00)	.776/(19.70)
10	1.215/(30.85)	1.063/(27.00)	.894/(22.70)
11	1.333/(33.85)	1.181/(30.00)	1.012/(25.70)
12	1.451/(36.85)	1.299/(33.00)	1.130/(28.70)




MATED MICRO-FIT CONNECTOR




RIGHT ANGLE THRU HOLE


- NOTES:
- HOUSING MATERIAL: 30% GLASS FILLED LIQUID CRYSTAL POLYMER (LCP), U.L. 94V-0, COLOR IS BLACK.
 - THIS HEADER MATES WITH MICRO-FIT RECEPTACLE #43645-****.
 - THIS HEADER IS DESIGNED IN METRIC.
 - SEE SHEETS 1 THRU 5 FOR RIGHT ANGLE ASSEMBLIES AND THEIR RESPECTIVE PART NUMBERS.
 - SEE SHEETS 6 THRU 10 FOR VERTICAL ASSEMBLIES AND THEIR RESPECTIVE PART NUMBERS.
 - TERMINAL PLATING:
 - "A": .000100/(0.0025) BRIGHT TIN-LEAD (90/10) OVER .000030/(0.00076) NICKEL.
 - "B": .000015/(0.00038) GOLD IN SELECTIVE AREA, AND .000050/(0.0013) TIN-LEAD (90/10) IN SELECTIVE AREA, BOTH OVER .000030/(0.00076) NICKEL.
 - "C": .000030/(0.00076) GOLD IN SELECTIVE AREA, AND .000050/(0.0013) TIN-LEAD (90/10) IN SELECTIVE AREA, BOTH OVER .000030/(0.00076) NICKEL.
 - DESIGNED FOR .062(1.57) THICK P.C. BOARDS.
 - ALL CONNECTORS MUST MEET THE PERFORMANCE REQUIREMENTS OF MOLEX PRODUCT SPECIFICATION PPS-43650.
 - TRAY PACKAGING SPECIFICATIONS ARE SHOWN ON DRAWING* PK-70873-0321.




RIGHT ANGLE THRU HOLE HEADER ISO VIEW



RECOMMENDED P.C. BOARD LAYOUT FOR 4 THRU 12 CIRCUIT HEADER



RECOMMENDED P.C. BOARD LAYOUT FOR 3 CIRCUIT HEADER



RECOMMENDED P.C. BOARD LAYOUT FOR 2 CIRCUIT HEADER

F	E2	REVISE PER UCR2000-0446 (19/99) 02/21/99
E2	E1	REVISE PER EON #43650-0511 99-03-05 A.GUZZIK
E1	E1	REVISE PER EON #43650-0541 99-02-27 A.GUZZIK
E	E1	REVISE PER EON #43650-0711 99-08-10 A.GUZZIK
D2	E1	REVISE PER EON #43650-0811 97-07-10 A.GUZZIK
D1	E1	REVISE PER EON #43650-0911 97-05-15 A.GUZZIK
D1	E1	REVISE PER EON #43650-1011 96-10-03 A.GUZZIK
D	E1	REVISE PER EON #43650-1111 95-08-20 A.GUZZIK
C	E1	REVISE PER EON #43650-1211 95-08-20 A.GUZZIK
C	E1	FINAL RELEASE EON #43650-03 95-05-01 A.GUZZIK
B	E1	RELEASE EON #43650-01 95-10-16 A.GUZZIK
B	E1	REVISING

CONNECTIONS SHOWN METRIC (INCH)

SCALE: 1:1

DATE: 02/21/99

DESIGNED BY: []

CHECKED BY: []

APPROVED BY: []

DATE: 02/21/99

REV: 0

REVISE ONLY ON CAD SYSTEM

TITLE: MICRO-FIT (3.0) 2 THRU 12 CIRCUIT IN-LINE HEADER ASS'Y.

MOLEX INCORPORATED

SEE CHART SDA-43650-****

FOR ORDERING CONSULTING INFORMATION VISIT US AT: WWW.MOLEX.COM


MOLEX INCORPORATED

1000 EAST 17TH AVENUE, SUITE 100, DENVER, CO 80202


TEL: 303.751.4000 FAX: 303.751.4001

ASSEMBLY ITEM NUMBER	PART CHARACTERISTICS FOR RIGHT ANGLE	
	NUMBER OF POSITION	PLATING OPTION
43650-0206	02	A
43650-0207	02	B
43650-0208	02	C
43650-0306	03	A
43650-0307	03	B
43650-0308	03	C
43650-0406	04	A
43650-0407	04	B
43650-0408	04	C
43650-0506	05	A
43650-0507	05	B
43650-0508	05	C
43650-0606	06	A
43650-0607	06	B
43650-0608	06	C
43650-0706	07	A
43650-0707	07	B
43650-0708	07	C
43650-0806	08	A
43650-0807	08	B
43650-0808	08	C
43650-0906	09	A
43650-0907	09	B
43650-0908	09	C
43650-1006	10	A
43650-1007	10	B
43650-1008	10	C
43650-1106	11	A
43650-1107	11	B
43650-1108	11	C
43650-1206	12	A
43650-1207	12	B
43650-1208	12	C


CKT. NO.	DIM. "A"	DIM. "B"	DIM. "C"
2	.270/(6.85)	.118/(3.00)	NA
3	.388/(9.85)	.236/(6.00)	NA
4	.506/(12.85)	.354/(9.00)	.185/(4.70)
5	.624/(15.85)	.472/(12.00)	.303/(7.70)
6	.742/(18.85)	.591/(15.00)	.421/(10.70)
7	.860/(21.85)	.709/(18.00)	.539/(13.70)
8	.978/(24.85)	.827/(21.00)	.657/(16.70)
9	1.096/(27.85)	.945/(24.00)	.776/(19.70)
10	1.215/(30.85)	1.063/(27.00)	.894/(22.70)
11	1.333/(33.85)	1.181/(30.00)	1.012/(25.70)
12	1.451/(36.85)	1.299/(33.00)	1.130/(28.70)




- NOTES:**
- HOUSING MATERIAL: 30% GLASS FILLED LIQUID CRYSTAL POLYMER (LCP), UL 94V-0, COLOR IS BLACK.
 - THIS HEADER MATES WITH MICRO-FIT RECEPTACLE *43645-****.
 - THIS HEADER IS DESIGNED IN METRIC.
 - SEE SHEETS 1 THRU 5 FOR RIGHT ANGLE ASSEMBLIES AND THEIR RESPECTIVE PART NUMBERS.
 - SEE SHEETS 6 THRU 10 FOR VERTICAL ASSEMBLIES AND THEIR RESPECTIVE PART NUMBERS.
 - TERMINAL PLATING:
 - 'A' = .000100/(0.0025) BRIGHT TIN-LEAD (90/10) OVER .000030/(0.00076) NICKEL.
 - 'B' = .000015/(0.00038) GOLD IN SELECTIVE AREA, AND .000050/(0.00127) TIN-LEAD (90/10) IN SELECTIVE AREA, BOTH OVER .000030/(0.00076) NICKEL.
 - 'C' = .000030/(0.00076) GOLD IN SELECTIVE AREA, AND .000050/(0.00127) TIN-LEAD (90/10) IN SELECTIVE AREA, BOTH OVER .000030/(0.00076) NICKEL.
 - DESIGNED FOR .062/(1.57) P.C. BOARD.
 - ALL CONNECTORS MUST MEET THE PERFORMANCE REQUIREMENTS OF MOLEX PRODUCT SPECIFICATION *PS-43650.
 - TRAY PACKAGING SPECIFICATIONS ARE SHOWN ON DRAWING* PK-70873-032L.




MATED MICRO-FIT CONNECTOR




RIGHT ANGLE SURFACE MOUNT (WITH MOLDED RETENTION PEG)




RIGHT ANGLE SURFACE MOUNT HEADER ISO VIEW



RECOMMENDED P.C. BOARD LAYOUT FOR 4 THRU 12 CIRCUIT HEADER



RECOMMENDED P.C. BOARD LAYOUT FOR 3 CIRCUIT HEADER



RECOMMENDED P.C. BOARD LAYOUT FOR 2 CIRCUIT HEADER

REVISIONS	REV. 1	DATE	05/11/21
DESCRIPTION	MICRO-FIT (3.0) 2 THRU 12 CIRCUIT IN-LINE HEADER ASS'Y.		
DATE	05/11/21	BY	CP
APP'D	SEE CHART SDA-43650-****		
SCALE	4:1		