



PDM: Rev:K STATUS: Released Printed: Aug 11, 2007

POWER SIGNAL PRODUCT No. ROWS EΙ РΙ P2 Ρ4 Ρ9 PIO UUUUUUUUU TTTTTTTT SSSSSSSS RRRRRRRRR 5 | 40 | - X X 0 0 | . NOTE: 8 В POWF R SIGNAL PRODUCT No. ROWS ΕI РΙ P2 Р3 P 4 P 5 Р6 P7 Р8 Ρ9 PIO PII PI2 PI3 PI4 1 2 3 4 5 6 7 8 UUUHUUUU TTTGTTTT 5 | 40 | - X X 0 0 2 \_ . C NOTE: 8 B PCB - NOTES I. ALL DIMENSIONS ARE BASIC UNLESS OTHERWISE SPECIFIED. 2. ALL THROUGH HOLES ARE LOCATED WITH A TRUE POSITION OF .004

3. ALL HOLE DIAMETERS ARE FINISHED HOLE SIZE

4. Ø 0.098/2.49 THROUGH HOLES ARE UNPLATED

5. Ø.0453/I.151 DRILLED HOLES PLATED WITH .0003/.007 MIN S∩Pb

OVER .001/1.03 to .003/.08 PLATING TO ACHIEVE A .080±.003/1.02±.08 HOLE CONNECTORS - NOTES

6. HOUSING MATERIAL: UL94V-O GLASS-FILLED HIGH TEMP THERMOPLASTIC SIGNAL PIN MATERIAL: COPPER ALLOY

1|2

POWER CONTACT MATERIAL: COPPER ALLOY

"MANUFACTURER" NAME, P/N, AND DATE CODE TO APPEAR ON THIS SURFACE

8. PLATING:

51401-XXYYY: SIGNAL PIN:30u"/0.76um Au OVER 50u"/1.27um Ni ON THE CONTACT AREA AND 100u"/2.54um SnPb OVER 50u"/1.27um Ni ON THE TERMINATION AREA POWER PIN: 30 u "/0.76 um Au OVER 50 u "/1.27 um Ni ON THE CONTACT AREA AND 100u"/2.54um SnPb OVER 50u"/1.27um Ni ON THE TERMINATION AREA

51401-XXYYYLF: SIGNAL PIN:30u"/0.76um Au OVER 50u"/1.27um Ni ON THE CONTACT AREA AND 78u"/2.00um Sn OVER 50u"/1.27um Ni ON THE TERMINATION AREA POWER PIN: 30u"/0.76um Au OVER 50u"/I.27um Ni ON THE CONTACT AREA AND 78u"/2.00um Sn OVER 50u"/1.27um Ni ON THE TERMINATION AREA

PART NUMBER 51401-XXYYYLF MEETS EUROPEAN UNION DIRECTIVE AND OTHER COUNTRY REGULATIONS AS DECCRIBED IN GS-22-008.

THE HOUSING WILL WITHSTAND EXPOSURE TO 260° PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A CIRCUIT BOARD.

CODE	MAT	"M" ING IGTH	CONTACT TYPE
G	0.220	[5.59]	SIGNAL
Н	0.220	[5.59]	SIGNAL
R	0.270	[6.86]	SIGNAL
S	0.270	[6.86]	SIGNAL
T	0.270	[6.86]	SIGNAL
U	0.270	[6.86]	SIGNAL
PΑ	N/A	[N/A]	POWER
ΗА	N/A	[N/A]	HOLD-DOWN

mat'l code				tolerances unless otherwise specified				CUSTOMER			D	4									
ltr	ecn	no.	dr	de	ote		. X X±.01/.X±		. 3	COPY			FCI				www.fciconnect.com				
K					line		.XXX±.005/.X±.13			projec	tion		title		I	<u> 1</u> P	+ 3;	25			
							XXXX±.0020/.XXX±.00		(±.05	4	<del>)</del> +	:1	RIG	НΤ	-				HEADER		
						angles dr	C. B	AROT		0 - 98	INC		MM		ict family			PWRBLADE		code	
					engr chr		3. BROWN 12 30 30		12-30	0-98	INCH / MM		- IVI IVI	size	ize dwg no					213	
									scale   ;		А	514			0 1		SHEET 3 OF 3				
					appd	1.1			Н							<u>F 3</u>					
she	sheet		revision																		
inc	lex	sheet	1																		
										3			cag	e code	2	252	26		4		

3 |

form no. 7530-00I-I03

PDM: Rev:K

STATUS: Released

Printed: Aug 11, 2007

В

Α

1/2