

<h3>1305</h3> <p><b>1305-0-15-XX-47-XX-04-0</b> Press-fit in .061 mounting hole</p>	<h3>1306</h3> <p><b>1306-0-15-XX-47-XX-04-0</b> Press-fit in .061 mounting hole.</p>	<h3>7305</h3> <p><b>7305-0-15-XX-47-XX-10-0</b> Solder mount in .060 min. hole.</p>	<h3>0400</h3> <p><b>0400-0-15-XX-47-XX-04-0</b> Press-fit in .067 mounting hole.</p>
---	--	---	--

<h3>0335</h3> <p><b>0335-0-15-XX-47-XX-04-0</b> Hex press-fit in .064 plated thru hole</p>	<h3>4614</h3> <p><b>4614-0-31-XX-47-XX-04-0</b> Compliant press-fit in .040±.003 plated hole. For .060→.100 thick board.</p>	<h3>4615</h3> <p><b>4615-0-31-XX-47-XX-04-0</b> Compliant press-fit in .040±.003 plated hole. For .090→.130 thick board.</p>	<h3>7614</h3> <p><b>7614-0-31-XX-47-XX-04-0</b> Compliant press-fit in .040±.003 plated hole. For .060→.100 thick board.</p>
--	--	--	--

<h3>8401</h3> <p><b>8401-0-15-XX-47-XX-04-0</b> Hex press-fit in .063 plated thru hole</p>	<h3>2400</h3> <p><b>2400-0-15-XX-47-XX-04-0</b> Press-fit in .066 mounting hole.</p>	<h3>6857</h3> <p><b>6857-0-15-XX-47-XX-10-0</b> Press-fit in .061 mounting hole.</p>	<h3>9393</h3> <p><b>9393-0-15-XX-47-XX-10-0</b> Press-fit in .067 mounting hole.</p>
--	--	--	--

<p><b>SPECIFICATIONS</b></p> <p><b>SHELL MATERIAL:</b> Brass Alloy 360, 1/2 Hard</p> <p><b>CONTACT MATERIAL:</b> Beryllium Copper Alloy 172, HT</p> <p><b>DIMENSION IN INCHES</b> <b>TOLERANCES ON:</b> LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p><b>ORDER CODE: XXXX - X - 15 - XX - 47 - XX - XX - 0</b></p> <p><b>BASIC PART #</b> →</p> <p><b>SPECIFY SHELL FINISH:</b> →</p> <p><b>01</b> 200μ" TIN/LEAD OVER NICKEL <b>15</b> 10μ" GOLD OVER NICKEL</p> <p>↑</p> <p><b>SPECIFY CONTACT FINISH:</b> →</p> <p><b>01</b> 200μ" TIN/LEAD OVER NICKEL <b>14</b> 10μ" GOLD OVER NICKEL <b>27</b> 30μ" GOLD OVER NICKEL</p> <p>↑</p> <p><b>CONTACT</b></p> <p><b>#47 CONTACT (DATA ON PAGE 211)</b></p>
--	---