
REF

В

path no.



₽D

3,05 .120


5,49 .216 7,87 .310


1 2

11,94 .470

1,78 .070

용





SECTION	A-A

ma	tΊ. ι	cod	e			1				ınle		רווי	NDT2	/IFR		F		<u>. </u>					
						oth	ner	<u>vise</u>		<u>ecif</u>								"					
ltr	ecn	no	d۲	dα	te	.0 ± 0.25					(COP		www.fciconnect.com									
N	N08-0	0170	SH	10/0	9/08	linea	near .00 ± 0.13			oro jection			title 4 POS VERT. SNAP PEG										
								.000	±	0.05	<u> </u>	14											- 1
Н	ECR V61355 BC LDH 020CT96				ICT%	angles ± 2°						Ψ		7	PCB III MOD JACK ASS								5 Y
J	ECR V	V61824 LW GREEN 09JAN97				dr M CHENG 7/13/0				3/01	_ MM _			product family MODJACK							code		
K	\$00022 LOV 01/25/00			25/00	engr	М	CHE	NG	7/1	3/01	1		_	size	dw	g n	0		NAN				
L	N04-	N04-0102 YS 11/23/04			chr] W CITEING			7/18/01		scale		Α4	90511						she	et		
М	N08-0097 SH 09/25/08			25/08	pbba	J	HSI/	4	7/2	20/01				H4			700	711			101	f	
she	et	rev	ision	М	М																		
ino	ndex sheet 1 2		2																				

Α

POSITIONS

LOADED

ALL

ALL

CONTACT PLATING

GXT

30u" / ,76u Au

REMARKS


NOT TOOLED

NOT TOOLED


All rights stractly reserved. Reproduction or issue to my whatever is not permitted without written authority from Property of ©FCI ELECTRONICS Copyright FCI ELECT
repr without NICS
Au rights strictly reserved. whatever is not permitted Property of ©FCI ELECTRO
Au rignts strictly whatever is not p Property of ⊙FCI
whatever Property

		' -		
PRODUCT NO.	POSITIONS Loaded	CONTACT PLATING	NOTES	
90511-001 -001LF -001HLF	ALL	GXT	BLACK	
-002 -002LF -002HLF	ALL	30u* / ,76u Au	BLACK	11
-003 -003LF	ALL	GXT	GREY	
-004 -004LF	ALL	30u* / ,76u Au	GREY	(1)
-005 -005LF -005 <u>HL</u> F	ALL	50u* / 1,27u Au	BLACK	

^LLEAD FREE PRODUCT NO. MEETS PIP PROCESS PRODUCT NO.







DETAIL A NOTE 5

NOTES :

PRODUCT NO.

90511-101 -101LF

(11)

-101HLF -102

-102LF

-102HLF

- P/NO WITH DASH OXX -NORMAL WAVE SOLDERING APPLICATION. P/NO WITH DASH 1XX -1R REFLOW APPLICATION (NOT TOOLED).
- PACKAGING SPEC. BUS-14-164.
- SCRATCH MARKS ACCEPTABLE ON THESE SURFACES.
- JACK IS FOR 1,57/,062 THICK PCB.
- SHOULD THE JACK NEED TO BE DISMOUNTED FROM THE PCB, PLS REMOVE JACK AS PER RECOMMENDED METHOD HEREIN. (DETAIL A) NIPPING THE LEGS OF THE PEG TOGETHER IS DISALLOWED, DTHERWISE LEG BREAKAGE MAY DCCUR.
- THESE DIMENSIONS ARE TAKEN FROM THE TOP OF THE PEG.
- GXT IS 0,76um / 30u' MIN GXT WITH AU FLASH DVER 1,27 um /
- THE PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.
- THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A WAVE SOLDER APPLICATION WITH A 1.60mm MINIMUM THICK CIRCUIT BOARD.
- IF LF P/N PACKAGING MEETS GS-14-920 SPECIFICATION.
- EQUIVALENT THICKNESS AU AND GXT PLATING HAVE SAME FUNCTION AND THEY ARE ALTERNATIVE BY THE CUSTOEMR

ı	na:	t′l.	code	2							unle		CUS	MDT2	1ER		F	C),							
Į-	tr	ecn	no	dr	da	te	0 47	ler	erwise specified 0.25					COPY	1	FG www.fciconnect.com								om		
	N		\dashv				linea	r 🗀	,00		0.13		org	jec:	tion	title 4 POS VERT. SNAI								P PEG		
	+						angle	s	0.05 ± 000				$ \oplus \leftarrow $				PCB III MOD JACK A									
							dr	М	CHE		<u> </u>	3/01	MM		_	-:-	product family MDDJACK co									
							engr M CHENG 7/13/01 chr M CHENG 7/18/01							size ^ 4	1 ~ ~~~						NAN sheet					
				appa	J	J HSIA 7/20/0			0/01				A4			70	JII			20	f					
		-		sion	М	м					ļ															
Ļ	<u>nd</u>	ex	she	et_	1	2																				

В