


Features

- Ideally Suited for Automated Insertion
- For Switching and AF Amplifier Applications
- Ultra-Small Surface Mount Package
- Lead Free/RoHS Compliant (Note 2)
- "Green" Device (Note 4 and 5)

Mechanical Data

- Case: SOT-363
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Terminal Connections: See Diagram
- Marking: K3W (See Page 3)
- Ordering Information (See Page 3)
- Weight: 0.006 grams



SOT-363		
Dim	Min	Max
A	0.10	0.30
B	1.15	1.35
C	2.00	2.20
D	0.65 Nominal	
F	0.30	0.40
H	1.80	2.20
J	—	0.10
K	0.90	1.00
L	0.25	0.40
M	0.10	0.25
α	0°	8°
All Dimensions in mm		

Maximum Ratings @T_A = 25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Collector-Base Voltage	V _{CB0}	-50	V
Collector-Emitter Voltage	V _{CEO}	-45	V
Emitter-Base Voltage	V _{EBO}	-5.0	V
Collector Current (Note 1)	I _C	-100	mA
Peak Collector Current (Note 1)	I _{CM}	-200	mA
Peak Base Current (Note 1)	I _{BM}	-200	mA
Power Dissipation at T _{SB} = 50°C (Note 1)	P _d	200	mW
Operating and Storage Temperature Range	T _j , T _{STG}	-55 to +125	°C

Electrical Characteristics @T_A = 25°C unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
DC Current Gain (Note 3)	h _{FE}	220	—	475	—	V _{CE} = -5.0V, I _C = -2.0mA
Thermal Resistance, Junction to Ambient Air (Note 1)	R _{θJA}	—	—	625	°C/W	Note 1
Collector-Emitter Saturation Voltage (Note 3)	V _{CE(SAT)}	—	—	-100 -400	mV	I _C = -10mA, I _B = -0.5mA I _C = -100mA, I _B = -5.0mA
Base-Emitter Saturation Voltage (Note 3)	V _{BE(SAT)}	—	-700	—	mV	I _C = -10mA, I _B = -0.5mA
Base-Emitter Voltage (Note 3)	V _{BE}	-580	-665	-750	mV	V _{CE} = -5.0V, I _C = -2.0mA
Collector Cutoff Current	I _{CB0}	—	—	-15	nA	V _{CB} = -30V, I _E = 0
Emitter Cutoff Current	I _{EBO}	—	—	-4.0	µA	V _{CB} = -30V, T _j = 150°C
Gain Bandwidth Product	f _T	—	—	-100	nA	V _{EB} = -5.0V, I _C = 0
Collector-Base Capacitance	C _{CB0}	—	—	3	pF	V _{CE} = -5.0V, I _C = -10mA, f = 100MHz
Emitter-Base Capacitance	C _{EBO}	—	11	—	pF	V _{EB} = -0.5V, f = 1.0MHz

- Notes:
1. Device mounted on FR-4 PCB, 1 inch x 0.85 inch x 0.062 inch; pad layout as shown on Diodes Inc. suggested pad layout document AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
 2. No purposefully added lead.
 3. Short duration pulse test used to minimize self-heating effect.
 4. Diodes Inc.'s "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.
 5. Product manufactured with Date Code UO (week 40, 2007) and newer are built with Green Molding Compound. Product manufactured prior to Date Code UO are built with Non-Green Molding Compound and may contain Halogens or Sb2O3 Fire Retardants.




Fig. 1, Power Derating Curve




Fig. 2, DC Current Gain vs. Collector Current




Fig. 3, Collector Saturation Voltage vs. Collector Current





Fig. 4, Gain Bandwidth Product vs. Collector Current

Ordering Information (Note 6)

Device	Packaging	Shipping
BC857BS-7-F	SOT-363	3000/Tape & Reel

Notes: 6. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

Marking Information



K3W = Product Type Marking Code
 YM = Date Code Marking
 Y = Year ex: N = 2002
 M = Month ex: 9 = September

Year	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012
Code	N	P	R	S	T	U	V	W	X	Y	Z

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.