



JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF3222-24B	LCD HIGH OUTPUT WHITE 7400°k RGB	1100 @ 0°C	440	5 ± 1	28,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

	METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0				
	THIRD ANGLE PROJECTION DRAWN BY L. WENGSTROM APP'VD BY DATE FD 8/20/02	TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP		SIZE A SCALE NONE	FSCM NO. 55335 DRAWING NO. BF3222-24B
REV. NO. [] DESCRIPTION/ECO NUMBER [] APP'VD DATE []	- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		RELEASED DATE 8/20/02	REVISION DATE []	REV. NO. [] SHEET 1 of 1