



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 6720°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) AVERAGE
BF3228-21B	x = .315 y = .295	1190	475	5 ± 1	28,000 ± 10%	40,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

<p>METRIC THIRD ANGLE PROJECTION</p>	<p>DIMENSIONS ARE IN MILLIMETERS</p> <p>TOLERANCE UNLESS OTHERWISE SPECIFIED</p> <p>1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0</p>	<p>JKL COMPONENTS CORPORATION</p>										
		<p>TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP</p>										
<p>REV. NO.</p>	<p>DESCRIPTION/ECO NUMBER</p>	<p>APPVD DATE</p>	<p>DRAWN BY L. WENGSTROM</p>	<p>APPVD BY DATE J.K. 8/5/04</p>	<p>SIZE A</p>	<p>FSCM NO. 55335</p>	<p>DRAWING NO. BF3228-21B</p>	<p>SCALE NONE</p>	<p>RELEASED DATE 12/95</p>	<p>REVISION DATE 8/5/04</p>	<p>REV. NO. B</p>	<p>SHEET 1 OF 1</p>
<p>- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED</p>												

REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE
B	ELECTRICAL RATING CHANGES	8/5/04
A	BRIGHTNESS RATING CHANGES	8/20/97
	RELEASED	12/95