



JKL LAMP PART NUMBER	COLOR LCD HIGH OUTPUT WHITE 8800°k RGB	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) AVERAGE
BF3240-24B	x = .285 y = .278	1240	495	5 ± 1	28,000 ± 10%	40,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

 THIRD ANGLE PROJECTION	METRIC	DIMENSIONS ARE IN MILLIMETERS	 JKL COMPONENTS CORPORATION						
	TOLERANCE UNLESS OTHERWISE SPECIFIED		TITLE						
	1 PL +/- 0	2 PL +/- 0	MINIATURE COLD CATHODE FLUORESCENT LAMP						
	ANGLE +/- 0		SIZE	FSCM NO.	DRAWING NO.				
A	ELECTRICAL RATING CHANGES	8/4/04	A	55335	BF3240-24B				
	RELEASE AND CANCEL P-0105-05	8/1/01							
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	- CAD DRAWING -		SCALE	RELEASED DATE	REVISION DATE	REV. NO.	SHEET
			MANUAL REVISIONS NOT PERMITTED		NONE	8/1/01	8/4/04	A	1 OF 1