


Mini-Mox

0.25 Watt and 0.5 Watt Precision Thick Film Axial Terminal High Voltage/High Resistance



FEATURES

- RoHS compliant
- Wide resistance ranges
- Epoxy coating
- Metal oxide resistive element

APPLICATIONS

- Avionics
- Medical electronics
- High gain feedback applications
- Current pulse limiters
- Vacuum and space application

The Mini-Mox resistor is very versatile, covering a wide resistance range as well as a wide range of operating voltages. Provided with tolerances down to 1%, the Mini-Mox resistor works well in precision circuits.

SPECIFICATIONS

Material
Resistor: Metal Oxide
Coating: Epoxy
Core: Alumina
Terminals: Solder-coated axial.
 RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu

Electrical
Resistance Range:
 100K to 1,500MΩ
Power Rating: 0.25W to 0.5W
Voltage Rating: 500V to 1,000V
Tolerance: 0.1% to 20%
Operating Temperature:
 -55°C to +155°C
Max. Overload Voltage:
 1,000V (MOX200)
 1,500V (MOX300)
Max. Pulse Voltage:
 1,500V (MOX200)
 3,000V (MOX300)

Ohmite Series	Resistance Range (Ohms)	Power @25°C	Voltage Rating	Available Tolerances*	A ±0.5mm (in/mm)	B ±0.5mm (in/mm)	d ±0.05mm (in/mm)
MOX200	100K to 1,500M	0.25W	500V	0.1% to 20%	0.26" / 6.5	0.09" / 2.2	0.02" / 0.6
MOX300	100K to 2,500M	0.50W	1,000V	0.1% to 20%	0.35" / 9	0.13" / 3.3	0.03" / 0.65

*Some tolerances are not available over the entire resistance range.


STANDARD TEMP. COEFFICIENT OF RESISTANCE AVAILABLE TOLERANCES

Series	STANDARD TEMP. COEFFICIENT OF RESISTANCE			AVAILABLE TOLERANCES		
	100 PPM/°C	200 PPM/°C	300 PPM/°C	Tolerance	Maximum Value Available MOX200	Maximum Value Available MOX300
MOX200	100K-100MΩ	101M-1000MΩ	1001M-1500MΩ	0.10%	10MΩ	10MΩ
MOX300	100K-100MΩ	101M-1000MΩ	1001M-2500MΩ	0.25%	20MΩ	20MΩ
				0.50%	30MΩ	30MΩ
				1%-20%	1500MΩ	2500MΩ

PERFORMANCE DATA

Characteristic	Test Method	Specification
Short time overload	Rated Power x2.5, 5 sec.	±0.5% max.
Resistance to soldering heat	260°C ±5°C, 10 ±1 sec.	±0.5% max.
Temperature cycling	-55°C/+155°C, 5 cycles	±0.5% max.
Withstanding voltage	500 VDC, 60 ±10 sec.	±0.5% max.
Insulation resistance	500 VDC	10,000MΩ or more
Moisture resistance	40°C ±2°C, 90-95%RH, 1000 hr.	±1.5% max.
Load life	70°C ±3°C, 1000 hr.	±2% max.

DERATING



ORDERING INFORMATION

RoHS Compliant | Tape and reel 2500 qty./reel std.

MOX200001003FER

Mini Mox Series MOX-20000 or MOX-30000	Ohms First 3 digits are significant; 4th digit is multiplier (# of zeroes to follow). Examples: 10R2 = 10.2 ohms 1000 = 100 ohms 1503 = 150,000 ohms	Tolerance B = 0.10% G = 2% C = 0.25% J = 5% D = 0.5% K = 10% F = 1% M = 15% P = 20%
--	---	---

Check product availability at www.ohmite.com

Check product availability using the Worldwide Inventory Search at ohmite.com

TAPE AND REEL

