

TCXO P/N	Suffix	Freq (MHz)	Vdd, VDC	Temp Range, Deg C	TC Stability	RF Out, Vpp	RF Level Min, Vpp	Current, mA max	Freq Adjust Type	DC Adjust Vcenter, VDC	Freq Adjust Range, ppm min
OSC1212	A	12.8	3V +/- 10%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	B	12.8	3V +/- 10%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	C	12.8	5V +/- 5%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
	D	12.8	5V +/- 5%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
OSC1213	A	13	3V +/- 10%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	B	13	3V +/- 10%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	C	13	5V +/- 5%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
	D	13	5V +/- 5%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
OSC1214	A	14.85	3V +/- 10%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	B	14.85	3V +/- 10%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	C	14.85	5V +/- 5%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
	D	14.85	5V +/- 5%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
OSC1215	A	16.8	3V +/- 10%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	B	16.8	3V +/- 10%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	C	16.8	5V +/- 5%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
	D	16.8	5V +/- 5%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
OSC1216	A	19.2	3V +/- 10%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	B	19.2	3V +/- 10%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	C	19.2	5V +/- 5%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
	D	19.2	5V +/- 5%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
OSC1217	A	19.68	3V +/- 10%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	B	19.68	3V +/- 10%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.80	DC Freq. Adjust	1/2 Vdd	+/-10
	C	19.68	5V +/- 5%	-30 to 80C	+/-1.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10
	D	19.68	5V +/- 5%	-30 to 85C	+/-2.5ppm	Sinewave	0.8	1.85	DC Freq. Adjust	1/2 Vdd	+/-10