

TCXO P/N	Freq (MHz)	Vdd, VDC	Temp Range, Deg C	TC Stability	RF Out, Vpp	RF Level Min, Vpp	Current max, mA	Freq Adjust Type	DC Adjust Vcenter, VDC	Freq Adjust Range, ppm min/max
OSC1622A	13MHz	2.8VDC	-20 to 60C	+/-2.5ppm	Sinewave	0.8	1.5	DC Freq. Adjust	1.2 +/-1 VDC	+/-10 to +/-16
OSC1623A	19.68MHz	2.8VDC	-30 to 85C	+/-1.5ppm	Sinewave	0.8	1.5	DC Freq. Adjust	1.5 +/-1 VDC	+/-4.5 to +/-7.5
OSC1626A	13MHz	2.8VDC	-30 to 75C	+/-2.5ppm	Sinewave	0.8	1.5	DC Freq. Adjust	1.5 +/-1 VDC	+/-9 to +/-15
OSC1644A	19.44MHz	2.8VDC	-30 to 75C	+/-3ppm	Sinewave	0.8	2.0	DC Freq. Adjust	1.25 +/-1.15 VDC	+/-6 to +/-11
OSC1645A	19.2MHz	2.8VDC	-30 to 85C	+/-1.5ppm	Sinewave	0.8	1.5	DC Freq. Adjust	1.5 +/-1 VDC	+/-10 to +/-15
OSC1646A	26MHz	2.8VDC	-30 to 85C	+/-1.5ppm	Sinewave	0.8	1.8	DC Freq. Adjust	1.5 +/-1 VDC	+/-10 to +/-15